



SOMAY PRODUCTS, INC.

4301 NW 35TH AVENUE

MIAMI, FLORIDA 33142-4382, USA

Tel: 305-633-6333 Fax: 305-638-5524

Toll Free: 888-2-4-SOMAY

e-mail: paint@somay.com URL: <http://www.somay.com>

Since 1926 – Manufacturer of Decorative and Protective Paints and Waterproofing Coatings

**SOMAY “Premium” 100% Acrylic Latex “Eggshell” Finish
Product No. 383**

SOMAY No. 383 is an exceptional “Premium” quality, 100% Acrylic Resin Based, waterborne coating, that is ideal for application to properly prepared exterior and interior walls and trim surfaces whenever a durable, beautiful “Eggshell” finish is desired. It can be used on wood, metal surfaces such as aluminum windows and siding, galvanized and/or primed steel surfaces, vinyl siding, masonry surfaces such as stucco, brick, stone, plaster, wallboard, drywall, cement composition panels, architectural plastic and foam forms, gutters, drip strips, shingle siding, shutters, doors, trim, and decorative features – practically any kind of surface on a house.

This exceptionally high quality paint breathes, so it resists blistering, chipping, peeling flaking and chalking, providing much longer durability than “flat” finishes. It contains the maximum amount of mildewcide, biocides, etc. allowed by U.S. Laws & Regulations, so it is as resistant to the growth of mold and mildew on the surface of the coating as it is possible to make it.

SURFACE PREPARATION: The surface to which SOMAY No. 383 is to be applied **MUST be thoroughly clean** and completely free of anything which could adversely affect the adhesion of the coating to the surface, including: all previous coatings which are glossy, loose, scaling, chipping, flaking, blistering, powdering, peeling or chalking; all dust, dirt, soot, sand,

gravel, grease, oil, uncured or infirm tar, curing agents, parting compounds, wax, soap film, rust, oxidation or petroleum-based residue; lye, lime, chlorine, salt or salt film, calcimine, efflorescence, or any other chemically reactive substance; and **MUST** be free of all mold, mildew, fungus and other growing organism. Infirm surfaces **MUST** be made firm.

CLEANING: A high pressure (min. 2,500 P.S.I. at the tip) water blast should be used to thoroughly clean all exterior surfaces. Mildew and similar growths **MUST** be killed with a 2%-3% chlorine solution in water (e.g. “Clorox” diluted 1:1 with water), followed by a thorough rinse with clean water. Allow clean surfaces to dry thoroughly.

WARNING! Sanding or scraping to remove old paint manufactured prior to 1950 that contained lead pigment may generate lead dust. Exposure to lead dust may cause adverse health effects, especially in young children and pregnant women. To control exposure to lead dust use protective equipment, such as a properly fitted respirator, and follow proper cleanup procedures. For more information in the US, call the NATIONAL LEAD INFORMATION CENTER at 1-800-424-LEAD.

PRIME POROUS SURFACES: Porous surfaces such as wood, masonry, stucco, plaster, concrete, etc. may be primed with SOMAY “Prime & Seal” (Clear) or SOMAY “PST”, Primers,

Sealer, Topcoat (Clear), a versatile, universal, waterborne primer.

EXTERIOR STUCCO SURFACES

which were previously painted and have been pressure cleaned to remove the old, chalky paint, should be primed with SOMAY SURFACE CONDITIONER (White) using one (1) gallon (3.79 L) for every 200 sq.ft. (18.58 sq.m.) of surface. Allow to dry thoroughly.

FERROUS METAL (STEEL) SURFACES:

This paint can be applied directly to clean, weathered, galvanized steel surfaces, or to primed steel surfaces. Unprimed steel surfaces can be primed with SOMAY Ferrous Metal Primer.

DO NOT THIN: This paint SHOULD BE APPLIED FULL STRENGTH as it is supplied by SOMAY. NEVER THIN, DILUTE or ADULTERATE with any other material. Thinning will reduce the long-term durability and the mildew inhibitive qualities of the applied coating.

APPLICATION RATE: Whenever this paint is being applied without a prime coat, we recommend TWO (2) FULL COATS, each 2 mils (50.8 microns) thick be applied, providing a total dry film thickness for both coats of 4 mils (101.6 microns).

Apply first coat on a very smooth, nonporous surface, using one (1) gallon (3.79 L) to cover up to, but never more than, 225 sq.ft. (27.87 sq.m) with a 2 mils thick coating. Allow paint to dry thoroughly between coats.

Apply second coat again using one (1)

gallon to cover each 225 sq. ft. of surface with another 2 mil thick coating. The actual spreading rates will be considerably less on rough, textured and/or porous surfaces, in which case more material must be used to develop the desired dry film thickness of 4 mils over the entire surface.

APPLICATION METHOD: May be applied using a high quality brush, a very smooth, very short nap (1/8") roller, or airless spray equipment.

WEATHER CONSIDERATIONS: Apply only when both ambient and surface temperatures are above 50° F (10° C). Apply only when the weather will be fair for a sufficiently long time for the coating to dry. Before application, keep from freezing while in transit or storage. Store in cool areas protected from exposure to direct sunlight.

DRYING TIME: Drying time will vary depending on both ambient and surface temperature, relative humidity, wind or air movement, exposure to sunlight, thickness of coating applied, etc. Under ideal drying conditions, 50% (or lower) relative humidity, 75° F (24° C) or higher temperature, forms a dew or light shower-resistant membrane in approx. 60 minutes after application, and dries sufficiently in approx. two to four hours to permit the application of the second coat.

CLEAN-UP: Using clean water, IMMEDIATELY flush spills or drips from shrubbery, walkways, driveways, etc. Application tools and equipment may be cleaned with warm, soapy water before the coating dries.

* * *

CAUTION! Harmful if swallowed. Do not take internally. Close container after each use. Avoid prolonged contact with skin and breathing of vapors. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

KEEP FROM FREEZING while in storage or transit before application.

LIMITED WARRANTY / LIMITED LIABILITY:

SOMAY warrants that, at the time of purchase from SOMAY, its products meet the specifications which SOMAY establishes for them. Since results from the use of its products depend on factors beyond SOMAY's control, SOMAY DISCLAIMS ALL OTHER WARRANTIES, either expressed or implied, INCLUDING, but NOT limited to, WARRANTIES OF MERCHANTABILITY AND FITNESS for particular purposes. User must assume full responsibility for: (a) determining the suitability of the product for his intended use, (b) understanding and following instructions, (c) preparing the surface properly, (d) applying the product correctly, and (e) obtaining the results desired from the use of the product. SOMAY shall not be liable for any incidental or consequential damages arising from the use or misuse of its products. SOMAY's liability is always limited to the original purchase price paid to SOMAY. Purchase and/or use of the product constitutes complete acceptance of all the terms of this Warranty.

July 2003