



SOMAY PRODUCTS, INC.

4301 NW 35TH AVENUE

MIAMI, FLORIDA 33142-4382, USA

Tel: 305-633-6333 Fax: 305-638-5524

Toll Free: 888-2-4-SOMAY

e-mail: paint@somay.com URL: <http://www.somay.com>

Since 1926 – Manufacturer of Decorative and Protective Paints and Waterproofing Coatings

**SOMAY “Premium” 100% Acrylic Latex Semi-Gloss Enamel
Product No. 630**

PRODUCT USE: SOMAY “Premium” Heavy-Duty, Industrial Strength, 100% Acrylic Latex Semi-Gloss Enamel, SOMAY Product No. 630, is exceptionally durable and highly resistant to mildew. It provides superior protection for the exterior or interior surface on which it is applied; when cured, it is washable and easy to keep clean.

Because it is available in Custom Color Tint Bases, this paint is highly recommended for use in the custom color of your choice as a topcoat over the SOMAY "ROOF MASTIC" System, so you can make your sloped roof any color you wish.

RECOMMENDED: This paint is recommended for both exterior and interior surfaces that are properly prepared, such as concrete, stucco, masonry, stone, bricks, unglazed tile, cement tile, painted or unpainted plaster, drywall, wallboard, wood, primed metal, etc.

SURFACE PREPARATION: The secret of a successful painting job is proper surface preparation. Surfaces MUST be free of anything which could adversely affect the adhesion of this paint to the surface, including loose, scaling, peeling, blistering, chipping, cracking, flaking, chalking or powdering paint; dust, dirt, sand, soot, grease, oil, tar, wax, soap film or petroleum-based residue; lye, lime, chlorine, salt, calcimine, efflorescence, or any other chemically reactive substance; and must be completely free of all mold, mildew, fungus,

or any other growing organism of any kind. Infirm surfaces MUST be made firm.

Scrape off all loose, peeling, blistering, chipping, cracking or flaking paint. Wire brushing, pressure cleaning, power sanding or sandblasting may be used to remove powdering and chalking paint. To remove dirt, grease, etc., wash with water and detergent and then rinse thoroughly with clean water. To kill mold, mildew, fungus, etc., scrub with a solution made with one part of liquid household bleach to one part of water. Rinse thoroughly with clean water. Patch all cracks, and when dry, sand smooth and seal. You should have a completely clean and firm surface before any new paint is applied.

WARNING! Sanding or scraping to remove old paint manufactured prior to 1950 that contained lead pigment may generate lead dust. Exposure to lead dust may cause adverse health effects, especially in young children and pregnant women. To control exposure to lead dust use protective equipment, such as a properly fitted respirator, and follow proper cleanup procedures. For more information in the US, call the NATIONAL LEAD INFORMATION CENTER at 1-800-424-LEAD.

UNPAINTED WOOD SURFACES: Sand and seal knots. Countersink nails, putty holes, and seal. When the surface is properly prepared and completely clean and dry, apply one coat of this paint. Allow to dry before applying finish coat of this paint.

UNPAINTED METAL SURFACES: Be sure metal is clean and free of rust and oxidation. When the surface is properly prepared and completely clean and dry, apply a primer coat of **SOMAY Metal Primer**. Allow to dry thoroughly before applying this paint.

UNPAINTED MASONRY: New masonry surfaces can be painted as soon as the masonry has thoroughly set. Be sure all loose sand is removed before painting.

PREVIOUSLY PAINTED WOOD SURFACES: Scrape off all loose paint. Wire brushing or power sanding may be necessary to remove loose, powdery or heavily chalked paint. Spot prime all bare wood areas with this paint. Sand all glossy surfaces. Apply finish coats of this paint.

PREVIOUSLY PAINTED MASONRY SURFACES: Scrape off all loose paint. Wire brush to remove all powdering or chalking paint. If powdering or chalking come off on the hand when rubbed over the surface, then a coat of **SOMAY Surface Conditioner** should be applied, according to label directions, before applying this paint.

Patch all cracks. When dry, sand smooth and seal. Apply finish coats of this paint.

APPLICATION: Apply only at temperatures above 50° F. (10° C). Stir thoroughly before using and occasionally while using. Apply paint as it comes from the can. **DO NOT THIN or ADULTERATE** with any additives. Apply generously, using brush or roller. Avoid excessive brushing or rolling. For even longer lasting durability, we recommend a second coat of this paint be applied. Two thin coats are preferred to one thick coat.

COVERAGE: To develop a 2-mil dry film thickness at 90% Transfer Efficiency, apply at a rate of 275 square feet per gallon on a very smooth, non-porous surface. On a porous, rough or textured surface, a gallon should cover from 150 to 250 square feet.

DRYING TIME: Dries to the touch in about 30 minutes, under normal drying conditions @ 75° F and 50% relative humidity. Allow to dry approx. 2 or more hours, before applying a second coat.

CLEAN UP: Keep a damp cloth handy to wipe up spills immediately. Clean hands, brushes, rollers, tools and other equipment immediately after use in warm, soapy water.

* * *

CAUTION! Harmful if swallowed. Do not take internally. Close container after each use. Avoid prolonged contact with skin and breathing of vapors. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

KEEP FROM FREEZING while in storage or transit before application.

LIMITED WARRANTY / LIMITED LIABILITY: SOMAY warrants that, at the time of purchase from SOMAY, its products meet the specifications which SOMAY establishes for them. Since results from the use of its products depend on factors beyond SOMAY's control, SOMAY DISCLAIMS ALL OTHER WARRANTIES, either expressed or implied, INCLUDING, but NOT limited to, WARRANTIES OF MERCHANTABILITY AND FITNESS for particular purposes. User must assume full responsibility for: (a) determining the suitability of the product for his intended use, (b) understanding and following instructions, (c) preparing the surface properly, (d) applying the product correctly, and (e) obtaining the results desired from the use of the product. SOMAY shall not be liable for any incidental or consequential damages arising from the use or misuse of its products. SOMAY's liability is always limited to the original purchase price paid to SOMAY. Purchase and/or use of the product constitutes complete acceptance of all the terms of this Warranty.

July 2006