



**SOMAY PRODUCTS, INC.**  
4301 NW 35<sup>TH</sup> AVENUE  
MIAMI, FLORIDA 33142-4382, USA  
Tel: 305-633-6333 Fax: 305-638-5524  
Toll Free: 888-2-4-SOMAY  
e-mail: [paint@somay.com](mailto:paint@somay.com) URL: <http://www.somay.com>

---

Since 1926 – Manufacturer of Decorative and Protective Paints and Waterproofing Coatings

---

## PRODUCT SPECIFICATIONS

4/04

SOMAY Product Code: 890-01

SOMAY Product Name: SOMAY Elastomeric "WALL MASTIC"  
Sealer & Protector

SOMAY Color Name: "White"

All % by Weight

### PIGMENT

White (Titanium Dioxide)	17.00%	
Misc. (Carbonates, Silicates, etc.)	<u>18.43</u>	
<b>TOTAL PIGMENT</b>	<b><u>35.43%</u></b>	<b>35.43%</b>

### VEHICLE

Resin (Acrylic Emulsion/Polymer Blend)	46.75%	
Solvent (Water & Misc.)	14.94	
Misc. (incl. Surfactants, Dispersants, Preservatives, Mildewcides, Defoamers, Anti-freeze, Film Forming Aids, Driers, Coalescent Agents, etc.)	<u>2.88</u>	
<b>TOTAL VEHICLE</b>	<b><u>64.57%</u></b>	<b><u>64.57</u></b>

### TOTAL FORMULATION

100.00%

Total Weight per Gallon	11.50 lbs.
Total Volume Solids	48.00 %
Total Solids by Weight	62.83 %
Theoretical Coverage/gal. @ 1 Mil dry film thickness (DFT)	768.97 sq.ft.

4/04