



SOMAY PRODUCTS, INC.
4301 NW 35TH AVENUE
MIAMI, FLORIDA 33142-4382, USA
Tel: 305-633-6333 Fax: 305-638-5524
Toll Free: 888-2-4-SOMAY
e-mail: paint@somay.com URL: <http://www.somay.com>

Since 1926 – Manufacturer of Decorative and Protective Paints and Waterproofing Coatings

SOMAY Elastomeric "PATCH & SEAL"
Product No. 992

PRODUCT USE: SOMAY "PATCH & SEAL" is formulated to Patch, Seal, Caulk and Waterproof leaks in roof and wall surfaces. Because of its soft buttery consistency, you can easily and quickly fill cracks, seams, tears, splits, small holes, etc. After drying, **SOMAY "PATCH & SEAL"** should be top-coated with **SOMAY "ROOF MASTIC"**. **SOMAY "POLY-MESH"**, polyester reinforcing membrane, can be sandwiched between the first and second coats to make an even stronger, more flexible, and more durable waterproofing patch.

SURFACE PREPARATION: The secret of a successful painting job is proper surface preparation. Surfaces **MUST** be (1) Firm, (2) Clean and (3) Dry.

High-pressure water or steam should be used to clean all cracks, seams, holes, etc., as well as all adjacent surfaces of all dirt and loose particles. Otherwise, scrub surfaces clean with a solution of TSP and water, and rinse thoroughly. All mildew and similar growths **MUST** be killed with a 5% chlorine solution, followed by a clean water rinse.

After cleaning, the cracks and adjacent surface should be free of all dust, dirt, soot, grease, oil, salt, loose sand or gravel, fungus, mildew and other growths, as well as previous coatings which are powdering, chalking, flaking, scaling, peeling or blistering, and anything else which could adversely affect the adhesion of this coating to the surface.

If the surface to be coated is wet or damp, wait for it to dry or accelerate the drying by using a fan or a blower from a hair dryer or the exhaust from a vacuum cleaner.

PRIME surface with **SOMAY** Product No. 777, "PST" or 7751, "**PRIME & SEAL**" if (a) powder or chalk remains after cleaning; (b) surface (especially concrete or mortar) contains salts, lime or similar chemicals; or (c) there is evidence of efflorescence on the surface.

WARNING! Sanding or scraping to remove old paint manufactured prior to 1950 that contained lead pigment may generate lead dust. Exposure to lead dust may cause adverse health effects, especially in young children and pregnant women. To control exposure to lead dust use protective equipment, such as a properly fitted respirator, and follow proper cleanup procedures. For more information in the US, call the NATIONAL LEAD INFORMATION CENTER at 1-800-424-LEAD.

APPLICATION: SOMAY "PATCH & SEAL" must be applied full strength as it comes from the can. However, if you wish to reduce the viscosity of the **SOMAY "PATCH & SEAL"** to make it easier to apply, you can mix in a little **SOMAY "ROOF MASTIC"**, Product No. 842, which is made from the same resin system, and therefore will be completely compatible. **NEVER THIN, DILUTE, OR ADULTERATE** with any other material.

Apply with a brush, putty knife, or similar tool. **SOMAY "PATCH & SEAL"** should be worked into all pores, cracks and seams so they are completely filled and leave a smooth finish with the adjacent surfaces.

COVERAGE: One (1) gallon will cover approximately 50 sq.ft. at a 22 mil thickness. **SOMAY "PATCH & SEAL"** should be topcoated with two coats of **SOMAY "ROOF MASTIC"**, Product No. 842.

DRYING TIME: Under normal drying conditions, **SOMAY "PATCH & SEAL"** forms a dew and rain-resistant membrane in approximately 30 to 60 minutes after application, and dries sufficiently in approxi-

mately 24 hours to permit the application of a top coat of **SOMAY "ROOF MASTIC"**. A longer drying time will be required if the surface being coated is not completely dry, is colder than 50° F., if too thick a coat is applied, if the relative humidity is higher than 90%, if the air temperature is below 50° F., or if the air is calm.

CLEAN UP: Any material inadvertently dropped on shrubbery, walkways or driveways should be flushed off immediately with water, before product is allowed to "set". Clean hands, brushes, rollers, tools and other equipment immediately after use in warm, soapy water.

* * *

CAUTION! Harmful if swallowed. Do not take internally. Close container after each use. Avoid prolonged contact with skin and breathing of vapors. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

KEEP FROM FREEZING while in storage or transit before application.

LIMITED WARRANTY / LIMITED LIABILITY:

SOMAY warrants that, at the time of purchase from SOMAY, its products meet the specifications which SOMAY establishes for them. Since results from the use of its products depend on factors beyond SOMAY's control, SOMAY DISCLAIMS ALL OTHER WARRANTIES, either expressed or implied, INCLUDING, but not limited to, WARRANTIES OF MERCHANTABILITY AND FITNESS for particular purposes. User must assume full responsibility for: (a) determining the suitability of the product for his intended use, (b) understanding and following instructions, (c) preparing the surface properly, (d) applying the product correctly, and (e) obtaining the results desired from the use of the product. SOMAY shall not be liable for any incidental or consequential damages arising from the use or misuse of its products. SOMAY's liability is always limited to the original purchase price paid to SOMAY. Purchase and/or use of the product constitutes complete acceptance of all the terms of this Warranty.

August 2003