

SOMAY TRAFFIC SAFETY MARKING PAINTS

SPECIFICATION	SPEC. NO.	SOMAY PRODUCT CODE NUMBER	RESIN SYSTEM		SOLVENTS & CLEAN UP			COLORS				NON-REFLECTORIZED	REFLECTORIZED			TO MAKE REFLECTORIZED GLASS BEAD REQUIRED						DRY TIME (At 70° F)	HAZ MAT RED SHIPPING LABEL	WT./GAL. (LBS.) (APPROX)			
			ACRYLIC LATEX	ALKYD (OIL)	POLYVINYL-TOLUENE BUTADIENE (RUBBER)	WATER	MINERAL SPIRITS	XYLENE	WHITE	YELLOW	BLACK		BABY BUGGY GREEN	HANDICAPPED BLUE	PRE-MIXED BEADS	DROP-ON BEADS	BOTH PRE-MIX & DROP-ON BEADS	FED. GOVT. SPEC			# / gal. Specified						
																		TT-B-1325									
																		TYPE							GRADATION		
I	II	III	A	B	C																						
LOW INDEX	MEDIUM INDEX	HIGH INDEX	COARSE DROP-ON	FINE PRE-MIX	FINE DROP-ON																						
State of Florida	971-12.2 T1	443		X			X					X	OPT		X							6	45	X	12.0		
State of Florida	971-12.3 T2	445		X				X				X	OPT		X							6	45	X	12.5		
State of Florida	971-12.4 T3	480		X						X		X	NONE									60	60	X	10.1		
U. S. Fed. Govt.	TT-P-85	850		X			X	X				X	OPT				X	X				10	40	X	11.3		
U. S. Fed. Govt.	TT-P-87	870		X			X	X				X	X	X		X		X	X			5/5=10	40	X	14.4		
U. S. Fed. Govt.	TT-P-110	110		X			X		X			X	NONE									30	30	X	10.6		
U. S. Fed. Govt.	TT-P-115 TYPE I	115-1		X			X	X				X	X									6	30	X	10.7		
U. S. Fed. Govt.	TT-P-115 TYPE II	115-2			X		X	X				X	X									6	15	X	12.0		
U. S. Fed. Govt.	TT-P-1952 TYPE I	1952	X			X		X	X	X		X	OPT					X	X			10	20		10.8		
SOMAY		352	X			X		X				X	OPT										75			12.0	
SOMAY		315	X			X			X			X	OPT										75			12.5	
SOMAY		317	X			X				X		X	NONE										75			11.4	
SOMAY		319	X			X					X	X	OPT										75			12.6	
SOMAY		449		X			X					X	OPT										45	X		11.8	
SOMAY		467			X			X				X	OPT										15	X		11.5	
SOMAY		468			X			X	X			X	OPT										15	X		11.5	