



**SOMAY PRODUCTS, INC.**  
 4301 NW 35<sup>TH</sup> AVENUE  
 MIAMI, FLORIDA 33142-4382, USA  
 Tel: 305-633-6333 Fax: 305-638-5524  
 Toll Free: 888-2-4-SOMAY  
 e-mail: [paint@somay.com](mailto:paint@somay.com) URL: <http://www.somay.com>

Since 1926 – Manufacturer of Decorative and Protective Paints and Waterproofing Coatings

**SOMAY INDUSTRIAL COATINGS COSTS per Square Foot per Mil DFT (Theoretical)**

INDUSTRIAL COATINGS  August 1, 2011	Total % Volume Solids ± 2%	Sq. Ft./Gal. Spread Rate @ 1 Mil DFT	“Cash & Carry” Price per Gal. @ SOMAY	SOMAY Cost/Sq. Ft. @ 1 Mil DFT	Recom- mended Total Mils DFT	Total Cost /Sq.Ft. @ Recom- mended Mils DFT
<b>BITUMASTIC COATINGS</b>						
“Bitumastic” 50	68	1,091	\$ 39.99	4¢	18	62¢
“Bitumastic” 300M	74	1,187	58.99	5¢	16	80¢
<b>CARBOMASTICS</b>						
“Carbomastic” 15	90	1,444	\$112.99	8¢	5	39¢
“Carbomastic” 90	90	1,444	94.99	7¢	5	33¢
<b>EPOXIES</b>						
“Rustbond” Universal Primer	98	1,572	\$98.99	6¢	2	13¢
“Carboguard” 890	75	1,203	73.99	6¢	5	31¢
“Carboguard” 891	75	1,203	94.99	8¢	5	39¢
“Carboguard” 893	77	1,235	68.99	6¢	3	17¢
“Carboguard” 954HB	99	1,588	108.99	7¢	3	20¢
“Carboguard” A-788	100	1,604	107.99	7¢	125	8.31
<b>POLYURETHANES</b>						
“Carbothane” Clear Coats	60	962	\$102.99	11¢	2	24¢
“Carbothane” 134 HG-Gloss	70	1,123	104.99	9¢	2	19¢
“Carbothane” 133 HB-Satin	57	914	82.99	9¢	4	36¢
<b>PHENOLINES</b>						
Phenoline 187	63	1,011	\$100.99	10¢	5	48¢
<b>ZINC</b>						
“CarboZinc” 11	79	1,267	\$95.99	8¢	3	29¢
<b>ANDEK PRODUCTS</b>						
“Polaroof RAC”	94	1,508	\$71.99	5¢	30	1.64
“Rubberkote 1047”	58	930	54.99	6¢	30	1.84
<b>NO FIRE</b>						
“NO FIRE” A-18	63	1,011	\$118.99	12¢	6	75¢

Notes: DFT = Dry Film Thickness - the paint film remaining on the painted surface after the solvent or water in the paint has evaporated and the paint is dry. 1 Mil = 1/1000 of an inch or 25.4 microns (metric) thickness of paint film. By comparison, this typewriter paper is 2.5 mils or 62.50 microns thick. A normal application of acrylic (water) or alkyd (oil) paint is approx. 1 mil (25.4 microns) to 1.5 mils (38.1 microns) DFT. All spreading rates are theoretical based on Total Volume Solids and assume 100% transfer efficiency to a very smooth, non-porous surface that has been properly prepared. Customer must make allowances for surface roughness, porosity, applicator wastage, etc.

