



SOMAY PRODUCTS, INC.
 4301 NW 35TH AVENUE
 MIAMI, FLORIDA 33142-4382, USA
 Tel: 305-633-6333 Fax: 305-638-5524
 Toll Free: 888-2-4-SOMAY
 e-mail: paint@somay.com URL: <http://www.somay.com>

Since 1926 – Manufacturer of Decorative and Protective Paints and Waterproofing Coatings

SOMAY PAINT COSTS per Square Foot per Mil DFT

SOMAY PAINTS – “White” March 5, 2012	Total % Volume Solids ± 2%	Sq. Ft./Gal. Spread Rate @ 1 Mil DFT	“Cash & Carry” Price per Gal. @ SOMAY	SOMAY Paint Cost / Sq. Ft. @ 1 Mil DFT	Recom- mended Mils DFT	Cost /Sq. Ft @ Total Mils DFT
WATERPROOFING COATINGS						
842 "ROOF MASTIC" - White	51	831	\$23.99	3¢	40	1.20
814 Rubber Waterproof Coat	52	834	44.99	5¢	20	1.28
890 "WALL MASTIC" - White	48	769	23.99	3¢	8	0.24
HOUSE PAINTS (SATIN)						
8630 "Steri-Shield" 100% Acrylic	46	735	\$35.99	5¢	2	0.10
383 "Premium" 100% Acrylic	33	534	24.99	5¢	2	0.10
LATEX FLAT WALL PAINTS						
358 "Premium" "High-Hide" V/A	32	515	\$19.99	4¢	2	0.08
340 "Premium" Vinyl Acrylic	26	414	14.99	4¢	2	0.08
127 "Gator-Hyde" Vinyl Acrylic	22	347	12.99	4¢	2	0.08
HIGH GLOSS ENAMELS						
237 Polyurethane (Oil)	51	815	\$30.99	4¢	2	0.08
SATIN/SEMI-GLOSS ENAMELS						
630 "Premium" 100% Acrylic	38	611	\$28.99	5¢	2	0.10
624 Vinyl Acrylic Latex	31	497	17.99	4¢	2	0.08
230 100% Acrylic-Floors	30	492	22.99	5¢	2	0.10
ROOF PAINTS						
8630 "Steri-Shield" 100% Acrylic	46	735	\$35.99	5¢	2	0.10
682 100% Acrylic Semi-Gloss	28	453	23.99	5¢	2	0.10
345 "Premium" Acrylic Flat	29	459	14.99	3¢	2	0.06
CLEAR COATINGS						
775 Concrete Clear Sealer	24	385	\$29.99	8¢	2	0.16
770 Exterior Varnish w UVLA	42	674	39.99	6¢	2	0.12
PRIMERS / UNDERCOATERS						
553 Acrylic Latex Undercoater	40	648	\$18.99	3¢	2	0.06
530 Surface Conditioner	41	663	18.99	3¢	2	0.06
777 100% Acrylic "P S T"	20	*	15.99	4¢	1	0.08
7751 "PRIME & SEAL"	20	*	18.99	10¢	1	0.10

Notes: DFT = Dry Film Thickness – the paint film remaining on the painted surface after the solvent or water in the paint has evaporated and the paint is dry. 1 Mil = 1/1000 of an inch or 25.4 microns (metric) thickness of paint film. By comparison, a piece of copy paper is 2.5 mils or 62.6 microns thick. A normal application of acrylic (water) or alkyd (oil) paint is approx..1 mil (25.4 microns) to 1.5 mils (38.1 microns) DFT. All spreading rates are theoretical based on Total Volume Solids and assume 100% transfer efficiency to a very smooth, non-porous surface that has been properly prepared. Customer must make allowance for surface roughness, porosity, applicator wastage, etc.

*Recommended 200 sq.ft./gal. application rate.